

Study of Densification and Plastic Deformation Behaviour of Ultra-tough a-C/a-C:Cr Multilayer Coatings Under Indentation and Scratch Tests

馬廣仁, 簡錫新, 郭建煌, 黃書瑋, 趙崇禮

Ph.D. Program in Engineering Science

Engineering

ma600229@ms17.hinet.net

Abstract

Hard coatings is one of the most widely used methods to improve wear resistance of materials. In principle, hard coatings with a high modulus and hardness provide an opportunity to assure contact in the elastic state under conditions of low compressive loading. Unfortunately, the coatings with extremely high elastic modulus and hardness become more sensitive to cracks which release elastic energy. Normally the energy dissipated by elastic deformation or brittle fracture are negligible compared with the energy losses associated with plastic deformation.

Alternated a-C/a-C:Cr coatings were made by DC magnetron sputtering from graphite and Cr target in an argon discharge. Mechanical properties were measured by indentation and scratch tests. The columnar alternated a-C/a-C:Cr multilayers accommodate shear and normal forces by viscoelastic, plastic deformation and densification. The energy dissipated by a-C/a-C:Cr multilayer coatings may significantly disperse the

*Manuscript

[Click here to view linked References](#)

radial tensile stress developed at the sides of the indenter and hence avoid tensile cracks along the edge of the scratch tracks. Energy dissipation by the coatings also delays plastic deformation and pile up of the substrate materials and avoids premature partial ring crack development ahead of the indenter. The greater compliance

and fracture toughness of the a-C/a-C:Cr multilayer coatings allows greater strains or strain energy to be stored before coating failure, and hence significantly enhance the scratch critical load under scratch tests.

Keyword : a-C/a-C:Cr coatings, scratch, indentation, densification, plastic deformation.